

8008H-E 1 SATA 5 in one DVR T Series



Features

- Support 8ch 1080P non real-time encoding;
- Support AHD, TVI,CVI, CVBS, IP video input;
- HDMI/VGA simultaneous video output;
- Mini 1U Case, 1 SATA (Up to 6TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Support WEB, CMS, VMS, MYEYE Platform;

Parameters

	Model	8008H-E
System	processor	Hi3531A
Video	Codec	H.264
	Encode	8*1080P@12fps; 8*1080N
	Decode	4*1080P@12fps; 8*1080N
	Multi-mode	Analog: 8*1080P@12fps; 8*1080N Hybird: 4*1080P(analog)+4*1080P(ip) IP: 4*5M; 4*3M; 8*1080P+8*960P; 16*960P
Audio	Playback	8ch
	Compression	G.711a
Management	Intercom	Support
	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
Interface	Backup	Network, USB, SATA
	Video input	8*BNC(Support Coaxitron)
	HDMI output	1*HDMI (MAX:1080P)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	4/1
	Alarm I/O	0/0
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
General	HDD	1*SATA interface (Up to 6TB)
	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/2A
	Consumption	<10W(Without HDD)
	Weight	Around 2KG
Dimension	255(L)* 236mm(W)* 44mm(H)	

Model:

8008H-E

Interface:

