



NVR - 8CH :

- ◆ Support 8ch 1-5MP IP Camera; HDMI support: 4K Output
- ◆ Free P2P Cloud Service, Plug & Play
- ◆ Motion Detection with Email Alert
- ◆ Remote View & Control, Anywhere, anytime.
- ◆ Support Android Mobile, Tablets, iPhone, iPad.



Model		NVR VSS 8
Chipset		Hi3536
RAM		1.5GB DDR3
OS		Embedded Linux
Video&Audio input	Bidirectional Talk	1CH,RCA(Line in,2Vp-p,1Kohms)
	Incoming bandwidth	96Mbps
	IPC Input	8CH
	VGA	1CH,1920×1080,1366×768,1280×1024,1280×720,1024×768
	HDMI	Standard 2.0
		3840×2160,1920×1080,1366×768,1280×1024,1280×720,1024×768
	Audio Output	1CH,RCA(Line out,2Vp-p,300ohms)
Video&Audio encoding	Audio Compression	G.711A
	Audio Bit Rate	64Kbps
Video&Audio decoding	IP channel Resolution	Main stream:Up to 3264x2448 Auxiliary stream:D1
	Video decoding	H.264/H.265
	Audio decoding	G.711A, G.726
	Synchronous Playback	Up to 8CH
	Decoding Ability	8CH 1440P@30FPS
Intelligent Analysis		1CH Face detection or 2CH Perimeter detection Up to 1080P
Other Function	Bidirectional Talk	Two-way voice intercom function
	Motion Detection	Zones: 396(22*18),Sensitivity: 1~6 (level 6 is highest)
	Picture Capture	Support JPEG Capture
HDD Interface	SATA	2 SATA Interfaces
	Max Capacity	Unlimited
	Interface	8 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces
	Supported standard	IEEE 802.3af
	Power	≥60W
External Interface	Network Interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet interface
	USB	2 USB2.0 Interfaces
Structure	Dimensions	405*365*123mm
	Size	1U,360*311.5*48mm
	Weight	3KG(without HDD)
	Installation	Desktop Installation
General	Power Supply	110V~220V±10%, 47Hz~63Hz
	Working Temperature	0 --+55
	Working Humidity	10%--90%
	Consumption	20W(without HDD,without POE)