

## REVOLUTION 8 NEW



### **Feature:**

- Support VGA, HDMI full HD output simultaneously;
- support ONVIF; access third party;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support various mobile monitoring (iPhone, Android);
- Remote Access, With DNS (ARSP),easy to monitor remotely

**Specification:**

	<b>Model</b>	Revolution 8 New
System	Main processor	Hi3520D V300
Interface	Preview	1/4/8/9
Video	Codec	H.264
	Monitor quality	VGA,HDMI: HD
	Preview ability	8*1080N
	Encode ability	8*1080N@12fps/4*1080P@15fps
	Decode ability	8*1080N@12fps/4*1080P@15fps
	Multi-mode input	analog: 8*1080N; 4*1080P hybrid: 2*1080P (analog) +2*1080P (network) ; 4*1080N (analog) +4*960P (network) network: 16*1080P; 9*1080P;16*960P; 4*5M
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	8ch(analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USBhard disk, USB burner, SATA burner
External Interface	Video input	8ch BNC
	Video output	1ch VGA, 1ch HDMI
	Loop Vout	N/A
	Audio I/O	1 (Can be extended to4ch) /1
	Alarm I/O	0 (Can be extended to 4ch) /0 (Can be extended to 1ch)
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	0 or 1*RS485, Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	1 pr 2*SATA ports (Max 6TB/per)
	Wireless	3G WIFI (extend via USB)
	General	Power supply
Power Consumption		<15W (without HDD)
Working environment		Temperature:0℃—+55℃, Humidity:10%—90%, Atm:86kpa—106kpa
Dimension		200*210*45mm
Weight		413g