

HD-IP 2MP/5MP PTZ BULLET:VIGILANT 5X IP 5

* Total Metal housing, IP66

* A-B scan, tour available

* Support audio (optional)

* ONVIF GB/T28181;Support P2P function

* Support H.264/MJPEG compression,triple stream, video output

* Compatible with HIKVISION/DAHUA/Milestone/AEVISION/UC2 and AXXON platform



Specification	
Camera	
Model	VIGILANT-5X-IP-5
PTZ	(Auto:left and right, Auto:up and down)
Sensor	1/3" CMOS 5MP 3516D
Output pixel	4MP:2560×1920/30fps,5MP:15fps 4MP:2592×1520/25fps,5MP:15fps
Lens	5X f=2.7~13.5MM
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
S/N Ratio	>50dB
Dome	
Communications Protocol	TCP/IP,HTTP,NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,HTTPS,P2P
Software Control	IE, CMS, Management Platform
Video compression	H.264/H.265/M-JPEG
audio compression	G711, PCM
Mobile View(optional)	Android iPhone
Rotation Range	Pan:0°~220° , Tilt:-45°~40°
Rotation Speed	Pan:0~30°/s , Tilt:0~25°/s
Preset Points	220pcs presets (dwell time 01-60s interval available)
Guard Tours	3 groups(Max.16 points, dwell time user selectable)
AB scan range	Any point in range:-45°~40° and 0°~200°
AB scan speed	1-9 grades
Operating temperature	Outdoor: -40℃~+60℃
Operation menu	English
Consumption	≤15W
Lightning Protection	Transient voltage 6000V
Related validation	IP66,CE,FCC,RoHs
IR parameters	
Auto Control IR LED	PWM
IR distance	Up to 100 meters
LEDs	4 PCS Array 42Mil IR+2 PCS Laser LED
Support ambient light detection	IR illumination on 1-9 grades selectable