

HD-IP 2MP/4MP PTZ BULLET

- * Total Metal housing, IP66
- * A-B scan, tour available
- * Support audio (optional)
- * Support external POE or WIFI (optional)
- * ONVIF GB/T28181;Support P2P function
- * Support H.264/MJPEG compression,triple stream, video output
- * Compatible with HIKVISION/DAHUA/Milestone/AEVISION/UC2 and AXXON platform



Specification		
Camera		
Model	VIGILANT-5X-IP	VIGILANT-10X-IP
PTZ	(Auto:left and right, Auto:up and down)	(Auto:left and right, Auto:up and down)
Sensor	1/3" CMOS 2MP Sony323	1/3" CMOS 2MP Sony323
Output pixel	1920x1080/30fps 1920x1080/25fps	1920x1080/30fps 1920x1080/25fps
Lens	5X f=2.7~13.5MM	10X f=5.1mm~51mm
BLC	Support	
AGC	Auto/manual	
WB	Auto/manual/indoor/outdoor	
S/N Ratio	>50dB	
Dome		
Communications Protocol	TCP/IP,HTTP,NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,HTTPS,P2P	
Software Control	IE, CMS, Management Platform	
Video compression	H.264/H.265/M-JPEG	
audio compression	G711, PCM	
Mobile View(optional)	Android iPhone	
Rotation Range	Pan:0°~220° , Tilt:-45°~40°	
Rotation Speed	Pan:0~30°/s , Tilt:0~25°/s	
Preset Points	220pcs presets (dwell time 01-60s interval available)	
Guard Tours	3 groups(Max.16 points, dwell time user selectable)	
AB scan range	Any point in range:-45°~40° and 0°~200°	
AB scan speed	1-9 grades	
Operating temperature	Outdoor: -40℃~+60℃	
Operation menu	English	
Consumption	≤15W	
Lightning Protection	Transient voltage 6000V	
Related validation	IP66,CE,FCC,RoHs	
IR parameters		
Auto Control IR LED	PWM	
IR distance	Up to 100 meters	
LEDs	6 PCS Array 42Mil IR LED	4 PCS Array 42Mil IR+2 PCS Laser LED
Support ambient light detection	IR illumination on 1-9 grades selectable	