

4 IN 1 PTZ BULLET AHD/TVI/CVI/CVBS : VIGILANT 4-10X

- * OSD menu is available
- * Total Metal housing, IP66
- * A-B scan, tour available
- * Support audio (optional)
- * Support coaxical function
- * Real time transmission, lossless video
- * Support AHD/TVI/CVI/CVBS output



Specification		
Camera		
Model	VIGILANT-4X	VIGILANT-10X
PTZ	(Auto:left and right, Auto:up and down)	(Auto:left and right, Auto:up and down)
Sensor	1/3" CMOS 2MP SONY323	
Output pixel	1920x1080/30fps,1920x1080/25fps	
Lens	4X f=2.8~12MM	10X f=5.1mm~51mm
WB	Auto	Auto/Indoor/Outdoor/Manual
BLC	Support	
AGC	Auto/Manual	
S/N Ratio	>50dB	
Dome		
Rotation Range	Pan:0°~220° , Tilt:~45°~40°	
Rotation Speed	Pan:0~30°/s , Tilt:0~25°/s	
Auto Flip	Support	
Preset Points	220pcs preset(Dwell time 01-60s interval available)	
Guard Tours	3 groups (each group 16 preset、 dwell time and speed selectable)	
AB scan range	Any point in range:-45°~40° and 0°~200°	
AB scan speed	1-9 grades	
Signal Transfer	AHD/CVI/TVI/CVBS selectable	
Operating temperature	-40℃~+60℃	
Consumption	≤15W	
Lightning Protection	Transient voltage 6000V	
Related validation	IP66,CE,FCC,RoHs	
IR parameters		
Auto Control IR LED	PWM	
IR distance	Up to 100 meters	
LEDs	4 PCS Array 42Mil IR	4 PCS Array 42Mil IR+2 PCS Laser LED
Support ambient light detection	IR illumination on 1-9 grades selectable	