

## MACK 2V



### Key Features:

- 1.) HD IP Metal Bullet Camera(Super WDR+ tarlight)
- 2.) Plug and play tech(P2P)
- 3.) H.264/H.265 video encoding
- 4.) Support ONVIF2.3
- 5.) Offer CMS and Mobile APP
- 6.) Starlight+ Super WDR
- 7.) IR Leds: 2pcs IR Array Leds
- 8.) IR Range: 40m IR Range
- 9.) Outternal POE (+3.5USD)



Model	<b>MACK 2V</b>
Type	<b>HD IP Bullet camera</b>
Horizontal Resolution	2.0Megapixel Progressive CMOS
Image Sensor	1/2.8" SONY290+3516CV300 <b>Lower lux(Starlight+ Super WDR)</b>
Effective Pixels(HxV)	Main stream: 1920*1080
Mini illumination	0.01lux-sec
Frame Rate	2.0MP@25/30FPS
Network Port	1 RJ45 Ethernet interface, 10M/100M self-adaption
Network Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP
ONVIF	Support Onvif
Lens	<b>2.8-12mm Lens</b>
IR LEDs	<b>2pieces IR Array Leds</b>
IR Distance	<b>40 Meter</b>
Noise Reduction	<b>2D/3D Digital Noise Reduction</b>
Video Compression	H.264 / H.265 / MJPEG
Mobile Phone Monitor	Support iPhone, Windows, Android mobile view

<b>Motion Detect</b>	YES
<b>POE</b>	Optional(POE Power supply:48V)
<b>Operation Function</b>	Offer free CMS, Support Web setting, OSD, real-time video transmission, support motion detection and IO alarm linkage for front end shortage/Capture/playback/download, Support Central remind and image linkage after motion detection and IO alarm linkage, support MJPEG capture, Support unit client-side remote management software
<b>Operating Temperature</b>	-20 ~ 60°C( relative humidity: max95% )
<b>Power Voltage</b>	DC12V±10% / POE (802.3af)
<b>IP range</b>	IP67
<b>Material</b>	Aluminum alloy
<b>Net Weight</b>	1.05kg
<b>Dimension</b>	261(L)*90(W)*90(H)