

MACK 2DV



Key Features:

- 1.) HD IP Metal Dome Camera
- 2.) Plug and play tech(P2P)
- 3.) H.264/H.265 video encoding
- 4.) Support ONVIF2.3
- 5.) Offer CMS and Mobile APP
- 6.) IR Leds: 36pcs IR Leds
- 7.) IR Range: 30m IR Range
- 8.) POE (+3.5USD)



Model	MACK 2DV
Type	HD IP Dome camera
Horizontal Resolution	2.0Megapixel Progressive CMOS
Image Sensor	1/2.9" Sony IMX323 + Hi3516V300
Effective Pixels(HxV)	Main stream: 1920*1080
Mini illumination	0.01lux-sec
Frame Rate	2.0MP@25/30FPS
Network Port	1 RJ45 Ethernet interface, 10M/100M self-adaption
Network Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP
ONVIF	Support Onvif
Lens	2.8-12mm Lens
IR LEDs	36pieces IR Array Leds
IR Distance	30 Meter
Noise Reduction	2D/3D Digital Noise Reduction
Video Compression	H.264 / H.265 / MJPEG
Mobile Phone Monitor	Support iPhone, Windows, Android mobile view
Motion Detect	YES

POE	Optional
Operation Function	Offer free CMS, Support Web setting, OSD, real-time video transmission, support motion detection and IO alarm linkage for front end shortage/Capture/playback/download, Support Central remind and image linkage after motion detection and IO alarm linkage, support MJPEG capture, Support unit client-side remote management software
Operating Temperature	-20 ~ 60°C (relative humidity: max95%)
Power Voltage	DC12V±10% / POE (802.3af)
IP range	IP66
Material	Aluminum alloy
Net Weight	0.6kg
Dimension	120(L)*120(W)*90(H)