

Model number	SELENIUM 14
<b>Camera</b>	
Image Sensor	1/2.9" CMOS Image Sensor
Resolution	1440P(30/15fps)
Effective Pixels	3096(H) × 2202(V)Approx. 6.87M pixels
Resolution	AHD/HDCVI/HDTVI:4.0Mega Pixel,1440P, CVBS: 960H
Video Standard	PAL/NTSC (OSD)
Synchronization	Inter-Sync
<b>Night Vision</b>	
Infrared Distance	30M
IR LED	3 Array Led
IR Power On	CDS Auto Control
<b>Features</b>	
Sen Up	Off/X2/X4/X8/X16/X32
Day & Night mode	External control (Default) /AUTO/COLOR / B&W
UTC	Support
OSD Support	Support
WDR:	Digital WDR
Min. Illumination	0.0008Lux@(F1.2,AGC ON)
S/N Ratio	≥42dB
Electronic Shutter	AUTO : 1/50(60)~1/60,000
White Balance	Auto/Manual
AGC	0-20 steps
Video Output	AHD/TVI/CVI/CVBS Switch by dial code cable menu
Dynamic Range	120db
DNR:	Off/Low/Middle/High

Language:	Chinese/English/JPN/KOR/S polyglot
-----------	------------------------------------

## Lens

Focal Length	3.6mm
Lens Mount	M12
Lens Type	Fixed,4.0MP
Angle of View	Horizontal: 76.5° Vertical: 50°

## General

Type	Outdoor Metal Bullet Camera
Video Interface	BNC Cable
Power Supply	12 V DC±10%
Lightning protection	Support
Power Consumption	3.6W
Working Humidity	Relative humidity less than 90%
Operating Temp	-20°C to +50°C (- 14°F to 122°F )
Storage Temp.	-40°C to +60°C ( -40°F to 140°F )

